Grandstar www.grandstarcn.com — www.grandstarcn.com Grandstar 29/30

## 25 ST-320R/Q Slitting Machine ST-321R/Q Tape Divider



ST-320R/Q 分条机

ST-321R/Q 分条机

### 产品特点/Features:


- ◎ R型热切适用于化纤类织物的热切封边,L型冷切适用于棉织物的分切卷取。
- ◎ 由止动磁粉离合器被动控制退卷张力, 手动调节。
- ◎ 两边装有废边卷取装置。
- ◎ 采用国内最先进的电子计长控制仪,精度高。
- ◎ 采用液压抬刀,放刀,便于控制。
- © R type hot cut is suitable for nipped-up cloth edge of chemical fiber fabrics, the L-type cold cut is suitable for slitting the cotton fabric.
- © The unwinding tension is passively controlled by the stop magnetic powder clutch, which is manually adjusted.
- O Both sides are equipped with waste edge batching device.
- © Using the most advanced electronic length counter in China, it with highly accuracy.
- O Hydraulic knife easy to control the knife raise and put down.

### 主要规格及技术参数/Major specifications and technical parameters:

适用幅宽/ Applicable width	1800mm ~ 3600mm
卷取直径/ Take-up diameter	<350mm(more than 350mm need customized)
最小切割宽度/Minimum cutting width	35mm
切割速度/ Cutting speed	0-50m/min(frequency converter control)
纠编类型/ Correction type	液压/Hydraulic
主机功率/Main power	1.5+2.2(kw)
整机功率/Machine power	<4kw(according to the heating knife)
张力控制/Tension control	Dual frequency converter+ Magnetic powder clutch

# 26 Belt Conveyors





- ◎ 本输送机停放时尺寸:高度为2米,长度为45米-2米,宽度1米。
- ◎ 主电机 2HP-4-380V
- ◎ 适宜布匹重量,每圈(捆)一般在25kg-60kg左右。
- ◎ 本输送机为移动式(网带有尼龙薄膜)
- ◎ 本产品适用于: 印染、针纺织等单位布匹运载。装货布、打圈 布、纱捆、散捆布等,时间快,工效高,减轻劳动强度,可减 少人员。
- ◎ 装载车型:集装箱车、箱式车、一般卡车。





- This belt conveyor can be raised 2 ~5 meters, the extension length could be 6.8~13 meters.
- The size when parked: 2\*1\*2m(L\*W\*H)
- © Main motor: 2HP-4-380V.
- © Suitable for the weight of each roll cloth: 25kg-60kg.
- This conveyor is mobile conveyor(net conveyor with nylon film)
- This product is suitable for carry cloth to reduce labor and improve the work efficiency.
- © suitable to load the container and truck.

### 27 KL-286ZD Flat Push Type Automatic Cloth Cutting Machine



### 适用范围/Scope of application:

平推式全自动切条机及直纹,45度斜纹卷布机适用于布料、无纺布、帐篷、雨伞、泡棉、皮革、反光材料、塑胶、纸张、双面胶、醋酸布、补强带、导电布、铜箔等材料各种宽度直条,横条及45度直斜条的卷布及裁切是服装、箱包、鞋帽、服装辅料、反光材料厂、帐篷厂、雨伞厂、电子厂等行业的理想选择。

Flat push type automatic cloth cutting machine diagonal grain cloth and 45-degree twill weave batching machine suitable for the fabric of: woven fabrics, unwoven fabrics, tents cloth, umbrellas cloth, foam, leather, reflective material, plastic, paper, double sided tape, acetate cloth, reinforced belt, conductive cloth, copper and other materials.

### 主要规格及技术参数/Major specifications and technical parameters:

TEMILICITY SETTING SPECIFICATIONS and technical parameters.	
布料幅宽/ Fabric width	1.7m/ 2.05m/ 2.4moptional
布料转速/ Speed	0-1200 RPM
切布直径/ Cloth Diameter	300mm(400mm Customizable)
布轴直径/ Fabric roll diameter	38mm
电机功率/ Motor power	1.5KW
刀片电机功率/ Motor power for cutter	1.5KW/2.2KW
最小切条宽度/ Minimum cloth cutting width	2mm
电压/ Voltage	380V/ 220V
外形尺寸/ Dimensions	2.8*1.5*0.85m